

**AMENDMENTS TO THE CLAIMS**

The following is a complete, marked up listing of revised claims with a status identifier in parentheses, underlined text indicating insertions, and strikethrough and/or double-bracketed text indicating deletions.

**LISTING OF THE CLAIMS**

1-24. (Canceled)

25. (Currently Amended) A computer readable medium having a data structure for managing a data area of the computer readable medium, the data area having a user area and a non-user area, the user area including a plurality of recording-units, the computer readable medium comprising:

a first management area storing a first data block including a plurality of sectors and a second data block including a plurality of sectors, the first management area being a temporary defect management area, the first data block having first information including recordation status indicating whether or not each recording unit of the user area has recorded data and the second data block having second information including a defect list, wherein respective last sectors of the first and second data blocks include third information including a first pointer pointing to an address where latest first information is recorded and a second pointer pointing to an address where latest second information is recorded; and

a second management area storing a latest first data block recorded in the first management area when no further recording ~~can be of~~ user data is made on the computer readable medium, the second management area being a defect management area.

26. (Canceled)

27. (Canceled)

28. (Canceled)

29. (Canceled)

30. (Canceled)

31. (Currently Amended) A method of recording management data on a recording medium, the recording medium including a data area having a user area and a non-user area, the user area including a plurality of recording-units, the method comprising:

recording a first data block including a plurality of sectors and a second data block including a plurality of sectors into a first management area, the first management area being a temporary defect management area, the first data block having first information including recordation status indicating whether or not each recording unit of the user area has recorded data and the second data block having second information including a defect list, wherein respective last sectors of the first

and second data blocks include third information including a first pointer pointing to an address where latest first information is recorded and a second pointer pointing to an address where latest second information is recorded; and

recording a latest first data block recorded in the first management area into a second management area when no further recording ~~can be~~ of user data is made on the recording medium, the second management area being a defect management area.

32. (Canceled)

33. (Canceled)

34. (Previously Presented) A method of reproducing data from a recording medium, the recording medium including a data area having a user area and a non-user area, the user area including a plurality of recording-units, the method comprising:

reproducing at least a portion of data recorded on the recording medium based on a first data block including a plurality of sectors and a second data block including a plurality of sectors recorded in a first management area of the recording medium when further recording can be made on the recording medium, the first management area being a temporary defect management area, the first data block including first information including recordation status indicating whether or not each recording unit of the user area has recorded data and the second data block having second information including a defect list, wherein respective last sectors of the first and second data blocks include third information including a first pointer pointing to

an address where latest first information is recorded and a second pointer pointing to an address where latest second information is recorded; and

reproducing at least a portion of data recorded on the recording medium based on a first data block recorded in a second management area of the recording medium when no further recording can be made on the recording medium, the second management area being a defect management area,

wherein the first data block recorded in the second management area is based on a latest first data block recorded in the first management area.

35. (Canceled)

36. (Canceled)

37. (Previously Presented) The computer readable medium of claim 25, wherein the first management area includes space to record a subsequent first data block having first information different from the first information in the first data block.

38. (Previously Presented) The computer readable medium of claim 37, wherein the first information in the subsequent first data block reflects changes in the recordation status since the first data block was recorded.

39. (Previously Presented) The method of claim 31, further comprising:

recording a subsequent first data block in the first management area, the subsequent first data block having the first information different from the first information in the first data block.

40. (Previously Presented) The method of claim 39, wherein the first information in the subsequent first data block reflects changes in the recordation status since the first data block was recorded.

41. (Previously Presented) The method of claim 34, wherein the first management area includes more than one of the first data blocks and the reproducing step reproduces based on a most recently recorded one of the first data blocks in the first management area.

42. (Previously Presented) The method of claim 41, wherein the most recently recorded one of the first data blocks includes a most current version of the first and third information.

43. (Previously Presented) The computer readable medium of claim 25, wherein only the respective last sectors of the first and second data blocks include the third information.

44. (Previously Presented) The method of claim 31, wherein only the respective last sectors of the first and second data blocks include the third information.

45. (Previously Presented) The method of claim 34, wherein only the respective last sectors of the first and second data blocks include the third information.

46. (Currently Amended) An apparatus for recording management data on a recording medium, the recording medium including a data area having a user area and a non-user area, the user area including a plurality of recording-units, the apparatus comprising:

a controller configured to control recording of a first data block including a plurality of sectors and a second data block including a plurality of sectors into a first management area, the first management area being a temporary defect management area, the first data block having first information including recordation status indicating whether or not each recording unit of the user area has recorded data and the second data block having second information including a defect list, wherein respective last sectors of the first and second data blocks include third information including a first pointer pointing to an address where latest first information is recorded and a second pointer pointing to an address where latest second information is recorded; and the controller being configured to control recording of a latest first data block recorded in the first management area into a second management area when no further recording ~~can be of~~ user data is made on the recording medium, the second management area being a defect management area.

47. (Previously Presented) The apparatus of claim 46, further comprising:

a drive configured to write the first data block into the first management area and to write the latest first data blocks into the second management area according to the control of the controller.

48. (Currently Amended) The apparatus of claim 46, wherein the controller is configured to control further recording of a defect list of a latest second data block recorded in the first management area into the second management area when no further recording of user data is ~~can be~~ made on the recording medium.

49. (Previously Presented) An apparatus for reproducing data from a recording medium, the recording medium including a data area having a user area and a non-user area, the user area including a plurality of recording-units, the apparatus comprising:

a controller configured to control reproducing at least a portion of data recorded on the recording medium based on a first data block including a plurality of sectors and a second data block including a plurality of sectors recorded in a first management area of the recording medium when further recording can be made on the recording medium, the first management area being a temporary defect management area, the first data block having first information including recordation status indicating whether or not each recording unit of the user area has recorded data and the second data block having second information including a defect list, wherein respective last sectors of the first and second data blocks include third information including a first pointer pointing to an address where latest first information is recorded and a second pointer pointing to an address where latest second information is recorded; and the controller configured to control reproducing at least a portion of data recorded on the recording medium based on a first data block recorded in a second management area of the recording medium when no further

recording can be made on the recording medium, the second management area being a defect management area,

wherein the first data block recorded in the second management area is based on a latest first data block recorded in the first management area.

50. (Previously Presented) The apparatus of claim 49, further comprising:

a drive configured to reproduce the first and second data blocks from the first management area and to reproduce the latest first data block from the second management area according to the control of the controller.

51. (Previously Presented) The apparatus of claim 49, wherein the controller is configured to control reproducing at least a portion of data recorded on the recording medium further based on a defect list recorded in the second management area of the recording medium when no further recording can be made on the recording medium, wherein the defect list recorded in the second management area is based on a latest second data block recorded in the first management area.

52. (Currently Amended) The computer readable medium of claim 25, wherein the second management area stores a defect list of a latest second data block recorded in the first management area when no further recording ~~can be of~~ user data is made on the computer readable medium.



53. (Currently Amended) The method of claim 31, further comprising:

recording a defect list of a latest second data block recorded in the first management area into the second management area when no further recording ~~can~~ be of user data is made on the computer readable medium.

54. (Previously Presented) The method of claim 34, further comprising:

reproducing at least a portion of data recorded on the recording medium further based on a defect list recorded in the second management area when no further recording can be made on the recording medium, wherein the defect list recorded in the second management area is based on a latest second data block recorded in the first management area.